




TLR-8® sub

**COMPACT RAIL-MOUNTED TACTICAL LIGHT WITH RED LASER**

**GLOCK® 43X MOS // GLOCK® 48 MOS // GLOCK® 43X RAIL // GLOCK® 48 RAIL (SUBCOMPACT HANDGUNS)**

- DESCRIPTION:** Ultra-lightweight & compact, the **TLR-8® sub** is a weapon-mounted tactical light with an integrated red laser. This light features the latest in LED technology for high-lumen operation and provides 1.5 hours of continuous run time from a single lithium battery. The specialized clamp system allows for mounting on GLOCK® 43X MOS, GLOCK® 48 MOS, GLOCK® 43X RAIL and GLOCK® 48 RAIL.
- CASE MATERIAL:** Body and face cap: 6000 Series machined aircraft aluminum with black anodized finish  
Switch housing: Impact- and chemical-resistant engineered polymer
- DIMENSIONS:** Width: 1.16 in (2.95 cm)      Height: 1.45 in (3.68 cm)      Length: 2.51 in (6.38 cm)
- WEIGHT:** 2.77 oz (78.5 g) with battery (included with purchase)
- LENS:** High temperature, shock-mounted, impact-resistant BOROFLOAT® glass
- LIGHT SOURCE:** LED: White, impervious to shock with a 50,000-hour lifetime.  
Laser: 640-660nm red laser
- LIGHT OUTPUT:** 500 lumens, 5,000 candela peak beam intensity and 141 m beam distance  
Custom TIR optic produces a concentrated beam with optimum peripheral illumination  
Optimized electronics provide regulated intensity
- ON/OFF:** Customizable rear switches left and right of trigger guard provide ambidextrous operation. Quick press for constant on operation and press and hold for momentary operation. Double tap either switch within ¼ of a second to activate strobe (if enabled).
- RUN TIME:** LED and LED/laser combined: 1.5 continuous hours to the 10% output level  
Laser only: 60 hours regulated output
- BATTERY:** One (1) 3-volt CR123A lithium battery with a storage life of 10 years
- FEATURES:** Ultra-lightweight and compact  
High-power LED for extreme brightness  
Ambidextrous operation  
One handed snap-on and tighten interface keeps hands away from muzzle when attaching or detaching  
Securely fits on GLOCK® 43X MOS, GLOCK® 48 MOS, GLOCK® 43X RAIL and GLOCK® 48 RAIL using the provided key and jaw set  
Extensively live fire tested  
Operating temperature: -40°F to +120°F  
IPX4-rated design; water-resistant operation  
Serialized for positive identification
- APPROVALS:**  Meets applicable United Kingdom and European Community Directives
- WARRANTY:** Streamlight's Limited Lifetime Warranty
- OPTIONAL ACCESSORIES:** Mounting adapters

All Rights Reserved. GLOCK® is a registered trademark of Glock, Inc. Streamlight has not sought endorsement of this product from Glock, Inc.

BOROFLOAT® is a registered trademark of SCHOTT AG.

EXPORT CONTROLS: The export of this product is subject to the jurisdiction of the U.S. Department of Commerce Export Administrative Regulations ("EAR"). The exported sale, transfer or shipment of this product is expressly prohibited by U.S. Law and is subject to export restrictions, including export licenses and accompanying documentation and authorization, the absence of which may result in fines and penalties. Furthermore, diversion, resale, re-export or transfer of this product is contrary to U.S. Law and is prohibited without the prior written consent of the U.S. Department of Commerce. Compliance with any and all export controls are the sole responsibility of the distributor.