



# SURVIVOR®

## SAFETY-RATED, RIGHT-ANGLE FIREFIGHTER'S FLASHLIGHT



Custom designed optic with optional, interchangeable Smoke-Cutter® plugs for preferred beam pattern:

- Black plug significantly reduces peripheral light for a tighter beam
- Amber plug reduces peripheral light and eye fatigue caused by glare

**Material/ Lens** Housing, base, and battery housing made from high-impact, super tough nylon offering exceptional durability. All openings are O-ring sealed for weather resistance. Spring-loaded clip with built-in D-ring easily attaches to belts and harnesses and reduces unwanted rotation. One-way valve for case venting. Available in safety orange, high-visibility yellow, or black

**Dims/Weight** Height: 7.06 in. (17.9 cm); Height in charger: 8.67 in. (22.0 cm); Width: 2.85 in. (7.24 cm); Diameter: 2.32 in. (5.89 cm)  
Grip area: Height: 3.6 in. (9.14 cm); Thickness: 1.35 in. (3.43 cm); Width: 2.20 in. (5.59 cm)  
NiMH: 18.0 oz (510 g) Alkaline: 13.7 oz (388 g)

**Light Source** White LED, impervious to shock with a 50,000-hour lifetime  
Custom Total Internal Reflection (TIR) optic for narrow beam and optimum peripheral illumination.

**Output/ Run Time** Four lighting modes:  
 • High: 175 lumens; 41,000 candela; 405m beam distance; runs 3.5 hours (NiMH); runs 4 hours (alkaline)  
 • Low: 60 lumens; 14,000 candela; 237m beam distance; runs 13 hours (NiMH); runs 15 hours (alkaline)  
 • Flash for signaling: runs 8 hours  
 • Moonlight mode provides low-level lighting for battery conservation: runs 20 days

**Switch** Rubber dome push-button actuator provides easy operation even when wearing heavy gloves

**Battery** Rechargeable NiMH battery; also accepts four (4) AA alkaline batteries





**Features** • Reduced bezel length to minimize snag hazards • IPX4-rated; water-resistant; 2m impact resistance tested  
 • Updated clip design for easy attachment to turnout gear • Super strong pocket clip

**Approvals\*** Class I & II, Division 1, Groups C, D, E, F, G; Class III, T-Code: T4  
 Class I, Division 2, Groups A, B, C, D; T-Code: T4  
 Flashlight meets 500°F requirements of NFPA 1971-8.6 (2018).  
 Charger meets requirements of NFPA 1900-11.1.11.2 (2024) mounted in any position.  
 MSHA: Permissible Flashlight, Approval No. 20-A150001-0.

**Warranty** Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse, and normal wear. We will repair, replace, or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches, and electronics which have a 2-year warranty with proof of purchase. THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL, OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW. You may have other specific legal rights which vary by jurisdiction. Visit [streamlight.com](http://streamlight.com) for full warranty information.

Description	UPC	Item #
Survivor - 230V AC/12V DC - Yellow	080926-90515-3	90515
Survivor - 230V AC/12V DC - Black	080926-90525-2	90525
Survivor - 230V AC/12V DC - Orange	080926-90505-4	90505
Survivor - 240V AC/12V DC - Yellow	080926-90516-0	90516
Survivor - 240V AC/12V DC - Orange	080926-90506-1	90506
Survivor - 240V AC/12V DC - Black	080926-90526-9	90526
Survivor - 120V AC/100V AC/12V DC - Yellow	080926-90513-9	90516
Survivor - 120V AC/100V AC/12V DC - Orange	080926-90503-0	90503
Survivor - 120V AC/100V AC/12V DC - Black	080926-90523-8	90523

Description	UPC	Item #
Survivor - (WITHOUT CHARGER) - Yellow	080926-90510-8	90510
Survivor - (WITHOUT CHARGER) - Orange	080926-90500-9	90500
Survivor - (WITHOUT CHARGER) - Black	080926-90520-7	90520
Survivor Alkaline Model - Yellow	080926-90541-2	90541
Survivor Alkaline Model - Orange	080926-90540-5	90540
Survivor Alkaline Model - Black	080926-90545-0	90545

ACCESSORIES			
	Description	UPC	Item #
	240V AUS AC Charge Cord	080926-22048-5	22048
	DC2 Direct Wire Charge Cord	080926-22050-8	22050
	DC1 Charge Cord	080926-22051-5	22051
	100V/120V AC Charge Cord	080926-22060-7	22060
	230V AC Charge Cord	080926-22061-4	22061
	240V AC Charge Cord	080926-22062-1	22062
	NiMH Battery Pack	080926-90339-5	90339
	Alkaline Battery Carrier (Batteries not included)	080926-90542-9	90542